

Tally DASCOM T2610+



High performance at low cost

- Its 680 cps print speed allows up to 20.000 pages per month
- Excellent print quality
- 15 million character ribbon
- Ethernet parallel and USB interface as standard
- User-friendly interface with backlight illuminated LCD display
- Epson FX 9-Needle Emulation

The Tally Dascom 2610 is a featured, reliable, and stylish machine. Performance, workload, maintainability, and excellent price ensure it is your only acceptable choice.

Continuous and cut forms fed quickly and easily to the front of the printer. This ensures a reliable paper transportation, even on 6-part stock.

The operator does not have to fumble over or around the printer to gain access to rear located tractors.

The printer operates with the highest reliability and performance and the least user intervention.

A lower acoustic rating results in a printer which is half as quiet as other competitive models.

Using the built-in Intelligent Mail® Barcode it is possible to get the best US Postal Service rates available



Intelligent Mail Barcode Sample

Available configurations:

T2610 Standard Product - 136 columns

SERIAL MATRIX

CARD PRINTERS

THERMAL PRINTERS

POS PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

Tally DASCOM T2610+

Print Speed	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
Resolution	Up to 360 x 360 dpi (ESC/P Emulation only)
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million strokes per pin
Standard Memory	256 kB
Standard Connectivity	Parallel (Bi-Directional IEEE 1284) Ethernet (10/100 Base T, Ipv6) and USB 2.0
Optional Connectivity	RS-232 Serial
Emulations	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9 needle Emulation
Optional Emulations	Neg TOF, Oki Data Barcode
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
Consumables	Ribbon: 15 million characters
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
Optional Paper Handling	Additional Push Tractor (rear)
Number of Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60 – 120 g/m ²
Paper Size	Width: 3" to 16.5" (76 mm – 420 mm) Length: 3" to 23.6" (76 mm – 600 mm)
Physical Weight	23.3 lbs (Approximately 10.6 kg)
Physical Size (W x D x H)	23.6" x 10.4" x 7.9" (600 x 265 x 200 mm)
Acoustic	Less than 53 dB(A)
Power Voltage	120 V or 240 V (auto-switching)
Power Consumption	60 Watts while Printing; less than 3 Watts while in power save
Temperature/Humidity	50 °F – 104 °F (+10 °C to +40 °C) 10% to 85% RH (not condensing)
Workload	Up to 25,000 pages per month
Reliability MTBF	20,000 hours
Drivers	Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP
Warranty	1 Year Return to Depot

DASCOM Americas
 34 Lakeview Court
 Verona, Virginia, 24482 . USA.
 Tel: +1 (877) 434-1377
www.dascomamericas.com
info.us@dascom.com

THERMAL PRINTERS

MOBILE PRINTERS

MATRIX PRINTERS

POS PRINTERS

ID PRINTERS